

MAXICHARGER™ AC FLOOR-STANDING SPECIFICATIONS



POWERFUL

Max 2*19.2kW, Simultaneous Charging of 2 Vehicles



ADVANCED

ISO 15118 Plug & Charge



CONVENIENT

Cable Management System



PROFITABLE

Generate Advertising Revenue Using 8 Inch High-Definition Screen



SMART

Dynamic Load Balancing



WORKPLACE | COMMERCIAL PARKING | CAR WORKSHOP

SPECIFICATIONS **MAXI**CHARGER AC FLOOR-STANDING

PRODUCT INFORMATION

INPUT/OUTPUT POWER RATING AND CURRENT	2*19.2kW (240V AC*80A) Output Amperage Adjustable Via Mobile App or DIP Switch, from 6A to 80A On Each Port
INPUT/OUTPUT VOLTAGE	208V±15%; 240V±15%, 60Hz
NETWORK TYPE	L1/N+PE, L1/L2/PE
INPUT CORD	Hardwired
CONNECTOR TYPE	SAE J1772, 25' (7.5m) or 16.4' (5m)
GROUND FAULT DETECTION	20mA CCID
PROTECTION	Over-Current, Over-Voltage, Under-Voltage, Integrated Surge Protection
CARD READER	Optional: ISO 15693, ISO 14443, NFC
POWER MEASUREMENT ACCURACY	+/- 1.0% from 1% to Full Scale

GENERAL CHARACTERISTICS

ENCLOSURE RATING	NEMA 3R
OPERATING ALTITUDE	6561 Ft.
OPERATING TEMPERATURE RANGE	-40F ~ +131F
STORAGE TEMPERATURE RANGE	-40F~+185F
MOUNTING	Floor Mounted or Wall Mounted
DIMENSIONS (H*W*D)	24.6"x12.6"x6.7" (625mm×320mm×170mm)

USER INTERFACE

STATUS INDICATION	LED/APP/LCD (8 Inch, 1280x720 Touch Screen)
USER INTERFACE	Autel Charge APP; Autel Charge Cloud
CONNECTIVITY	Bluetooth, Wi-Fi, Ethernet, 4G, RS485
COMMUNICATION PROTOCOLS	OCPP 1.6J (Can be Upgraded to OCPP 2.0.1 Later)
USER AUTHENTICATION	APP, RFID Card, Credit Cards (Optional)

SOFTWARE UPDATE

SOFTWARE UPDATE	OTA Updates Via Web Portal
-----------------	----------------------------

CERTIFICATIONS & STANDARDS

SAFETY & COMPLIANCE	UL 2231-1, UL 2231-2, UL2594, NEC Article 625, CSA C22.2, UL 916, ISO 15118 Plug&Charge
EMC COMPLIANCE	FCC 15 Class B
CERTIFICATION	Energy Star, OpenADR 2.0b
WARRANTY	36 Months, Warranty Extension Possible

